

TOPSERV® 600 VFD XLPE insulation, EMC-preferred type, highly flexible motor power supply cable, oil-resistant, NFPA 79 Ch. 4



Technical data

- XLPE-insulated motor supply cable acc. to UL Std. 1277 and 2277
- **Temperature range**
UL/CSA TC -40°C to +90°C
flexing +5°C to +50°C
static -40°C to +105°C
- **Nominal voltage**
UL/CSA TC 600 V
UL WTTC/Flexible Motor Supply 1000 V
- **Test voltage** 4000 V
- **Minimum bending radius**
flexing 10x cable Ø
permanently flexing 7,5x cable Ø
- **Coupling resistance**
max. 250 Ohm/km

Cable structure

- Finely stranded (Cl. M 18-10AWG; Cl. K 8-2 AWG), tinned copper acc. to AWG standards
- Special XLPE conductor insulation
- Black conductors with continuous white numbering
- GN-YE conductor in the outer layer
- Conductors stranded in layers with optimal lay length
- Overall non-woven separator
- Braided, tinned copper shield, approx. 85% coverage
- Separator
- Special TPE outer jacket
- Orange (RAL 2003) jacket
- With length marking in feet

Properties

- Self-extinguishing and flame retardant acc. to CSA FT4
- The materials used during manufacturing are cadmium-free, contain no silicone and are free from substances harmful to the wetting properties of lacquers
- UV-resistant
- Direct burial rated
- Resistant to cleaning and disinfecting agents acc. to



Tests

- **UL:**
TC-ER (1277), WTTC (2277), ITC-ER & PLTC-ER (18-12 AWG), 44 (14-2 AWG), NFPA 79 Ch. 4, Class I Div. 2 per NEC Art. 501, NEC Art. 336 & 392, Oil Res I/II, 90°C Dry/Wet, -40°C Cold Bend
- **CSA:**
C22.2 No. 230 & 239 - c(UL) CIC-TC FT4
C22.2 No. 210 - AWM I/II A/B FT4

Note

- VFD = Variable Frequency Drive
- **Available on request**
- Black (RAL 9005) jacket

Application

Highly flexible, extremely oil-resistant, thermoset-insulated motor supply cable for modern servomotors; the double-shielding with special aluminum foil (100% coverage) and tinned copper braid (approx. 85% coverage) provides effective protection against electrical disturbances and the resultant failures. XLPE insulation makes this compliant with the requirements outlined in the current edition of NFPA 79 Chapter 4. The special TPE jacket is extremely resistant to oil, coolants and solvents making it the perfect solution for industrial applications. Open, unprotected installation in cable trays and from cable trays to the machine, as well as in pipes and direct burial are approved.

EMC = Electromagnetic compatibility

To optimize the EMC features we recommend a large round contact of the copper braiding on both ends.

CE= The product conforms to EC Low-Voltage Directive 2006/95/EC.

Part no.	No. conductor x AWG No.	Cross section mm²	Outer Ø app. mm	Cop. weight kg / km	Weight app. kg / km
62616	4 x 18	0,824	11,9	60,9	182,0
62617	4 x 16	1,31	12,9	82,5	219,0
62618	4 x 14	2,08	14,5	115,2	290,0
62619	4 x 12	3,31	16,5	170,7	379,0
62620	4 x 10	5,26	18,0	239,3	484,0
62621	4 x 8	8,37	23,2	392,9	796,0
62622	4 x 6	13,3	24,9	606,6	1042,0
62623	4 x 4	21,2	28,0	921,9	1429,0
62624	4 x 2	33,6	32,0	1396,5	2009,0

Dimensions and specifications may be changed without prior notice.